

TECHNICAL DATA

Essential 1200 Felt Back Eco

DoP: 3558-1133-086-000



Technical Details

Manufacturing process	DIN ISO 2424	Tufted 1/10''
Frontside structure	DIN ISO 2424	Cut pile - Saxony
Color	DIN ISO 2424	Chromojet print
Pile Material		100% Polyamid PA 6 - Econyl
Primary backing	DIN ISO 2424	PP Woven
Secondary backing	DIN ISO 2424	Fe l t Back
Pile weight	DIN ISO 2424	approx. 1200 g/m²
Total weight	ISO 8543	approx. 2500 g/m²
Pile height	ISO 1766	approx. 6,0 mm
Total thickness	ISO 1765	approx. 9,5 mm
Number of knots	ISO 1763	approx. 213000 /m²
Width	DIN 3018	approx. 400 cm

Functional properties

Wear classification	EN1307:2014+A3:2018	33
Comfort rating	EN1307:2014+A3:2018	LC 5
Castor chair resistance	EN 985: Prüfung A	Class A

Physical properties

Fire rating	D I N EN 13501-1	Cfl-s1*
*glued on massive mineral concrete		

Fastnesses

Colour fastness to light EN ISO 105-B02:2013

Sustainability

Emissions TÜV ProfiCert Premium in Progress **EPD**

in Progress





Rev.: 001/06.2025