


## **TECHNICAL DATA**

# Soft 1150 Action Back LF

DoP: 3476-1606-063-000















#### **Technical Details**

Manufacturing process	DIN ISO 2424	Tufted 1/10"
Frontside structure	DIN ISO 2424	Cut pile - Saxony
Color	DIN ISO 2424	Chromojet print
Pile Material		100% Polyamid PA 6.6
Primary backing	DIN ISO 2424	PES Woven
Secondary backing	DIN ISO 2424	Action Back
Pile weight	DIN ISO 2424	approx. 1150 g/m²
Total weight	ISO 8543	approx. 2282 g/m²
Pile height	ISO 1766	approx. 8,0 mm
Total thickness	ISO 1765	approx. 9,2 mm
Number of knots	ISO 1763	approx. 169000 /m²
Width	DIN 3018	approx. 400 cm

#### **Functional properties**

Wear classification	EN1307:2019	23/31
Comfort rating	EN1307:2019	LC 4
Castor chair resistance	EN 985: Prüfung A	Class A

### **Physical properties**

Fire rating	DIN EN 13501-1	Bfl-s1*1
*glued on massive mineral concrete		

#### **Fastnesses**

Colour fastness to light	EN ISO 105-B02:2013	6-7
Colour fastness to water	DIN EN ISO 105 E01:2013	5
Rubbering fastness dry/wet	DIN EN ISO 105 X12:2002	5/5

