


Product description



Technical Details

| | | |
|-----------------------|--------------|--------------------------------|
| Manufacturing process | DIN ISO 2424 | Tufted 1/10" |
| Frontside structure | DIN ISO 2424 | Cut pile - Saxony |
| Color | DIN ISO 2424 | Chromojet print |
| Pile Material | | 100% Polyamid PA 6.6 |
| Primary backing | DIN ISO 2424 | PES Woven |
| Secondary backing | DIN ISO 2424 | Felt Back |
| Pile weight | DIN ISO 2424 | approx. 1150 g/m ² |
| Total weight | ISO 8543 | approx. 2782 g/m ² |
| Pile height | ISO 1766 | approx. 8,0 mm |
| Total thickness | ISO 1765 | approx. 10,7 mm |
| Number of knots | ISO 1763 | approx. 169000 /m ² |
| Width | DIN 3018 | approx. 400 cm |

Functional properties

| | | |
|-------------------------|-------------------|---------|
| Wear classification | EN 1307:2019 | 23/32 |
| Comfort rating | EN 1307:2019 | LC 5 |
| Castor chair resistance | EN 985: Prüfung A | Class A |

Physical properties

| | | |
|-------------|----------------|----------|
| Fire rating | DIN EN 13501-1 | Bfl-s1*1 |
|-------------|----------------|----------|

*glued on massive mineral concrete

Fastnesses

| | | |
|--------------------------|-------------------------|-----|
| Colour fastness to light | EN ISO 105-B02:2013 | 6-7 |
| Colour fastness to water | DIN EN ISO 105 E01:2013 | 5 |
| Rubbing fastness dry/wet | DIN EN ISO 105 X12:2002 | 5/5 |

