




Product description



Technical Details

Manufacturing process	DIN ISO 2424	Tufted 1/10"
Frontside structure	DIN ISO 2424	Cut pile - Saxony
Color	DIN ISO 2424	Chromojet print
Pile Material		100% Polyamid PA 6.6
Primary backing	DIN ISO 2424	PP Woven
Secondary backing	DIN ISO 2424	Felt Back
Pile weight	DIN ISO 2424	approx. 1600 g/m ²
Total weight	ISO 8543	approx. 3085 g/m ²
Pile height	ISO 1766	approx. 9,0 mm
Total thickness	ISO 1765	approx. 10,3 mm
Number of knots	ISO 1763	approx. 194775 /m ²
Width	DIN 3018	approx. 400 cm

Functional properties

Wear classification	EN 1307:2019	23/31
Comfort rating	EN 1307:2019	LC 5
Castor chair resistance	EN 985: Prüfung A	Class A

Physical properties

Fire rating	DIN EN 13501-1	Bfl-s1*
-------------	----------------	---------

*glued on massive mineral concrete

Fastnesses

Colour fastness to light	EN ISO 105-B02:2013	6-7
Colour fastness to water	DIN EN ISO 105 E01:2013	5
Rubbing fastness dry/wet	DIN EN ISO 105 X12:2002	5/5