




Product description



Technical Details

Manufacturing process	DIN ISO 2424	Tufted 1/10"
Frontside structure	DIN ISO 2424	Cut pile - Saxony
Color	DIN ISO 2424	Chromojet print
Pile Material		Polyamid PA 6 - Econyl
Primary backing	DIN ISO 2424	PP Woven
Secondary backing	DIN ISO 2424	Action Back
Pile weight	DIN ISO 2424	approx. 900 g/m ²
Total weight	ISO 8543	approx. 2000 g/m ²
Pile height	ISO 1766	approx. 5,0 mm
Total thickness	ISO 1765	approx. 7,0 mm
Number of knots	ISO 1763	approx. 198750 /m ²
Width	DIN 3018	approx. 400 cm

Functional properties

Wear classification	EN1307:2014+A3:2018	33
Comfort rating	EN1307:2014+A3:2018	LC 5

Physical properties

Fire rating	DIN EN 13501-1	Cfl-s1*
-------------	----------------	---------

* glued with a solvent-free dispersion adhesive on massive mineral concrete

Fastnesses

Colour fastness to light	EN ISO 105-B02:2013	7
--------------------------	---------------------	---

Sustainability

Emissions	TÜV ProfiCert Premium	NR. 707107640-1
EPD		in Progress



ECONYL®



ÖKOPROFIT
KlimaPakt
KREIS COESFELD